










<b>TECHNISCHE GEGEVENS</b> <b>PRODUCT-INFORMATION</b> <b>TECHNISCHE DATEN</b>	<h1><i>Dahna</i></h1>
<b>Kwaliteitsnaam</b> <b>Qualityname</b> <b>Qualitätsname</b>	
Productie methode Type of manufacture Herstellungsart	Getuft Tufted Getuftet
Deling Gauge Teilung	1/4"
Kwaliteitsbeschrijving Quality description Oberseitengestaltung	Lussenpool Looppile Schlinge
Poolmateriaal Pilematerial Nutzschicht	100% Scheerwol 100% New Wool 100% Schurwolle
Tuftdoek Primary backing Trägermaterial	PP weefsel PP fabric PP Gewebe
Rug Secondary backing Rückenbeschichtung	Jute
Poolhoogte Pileheight Polhöhe	9 mm
Totaal hoogte Total thickness Gesamthöhe	13 mm
Poolgewicht Pileweight Polgewicht	1750 g/m <sup>2</sup>
Totaal gewicht Total weight Gesamttgewicht	2800 g/m <sup>2</sup>
Breedte Width Breite	400 cm

Lichtechtheid Colourfastness to light Lichtechtheit	ISO 105 B02	5	
Waterechtheid Colourfastness to water Wasserechtheit	ISO 105 E01	4	
Wrijftechtheid Colourfastness to rubbing Reibechtheit	ISO 105 X12	Droog / Dry / Trocken 4,5	Nat / Wet / Nass 3
Watervlekkenechtheid Water stains fastness Wasserflekkenechtheit	EN 1307, annex G	4	

Toepassing / Classification / Eignungsbereich			
Toepassing Classification Eichnungsbereich	EN 1307	23 Heavy domestic use 32 General commercial use	 
Trap Stairs Treppe	EN 1963 , B		
Vlamwerend Flammability Brennklasse	ISO 11925-2	Class Dfl	 Dfl-s1
Comfort Comfort Komfort	EN 1307		
Prodis / GUT			
<b>EN 14041</b>			  Dfl-s1  DS
Beschermt tegen wol bederf Gegen Wollschädliche Geschützt Protected against wool pests			

Op alle specificaties zijn normale handelstoleranties van toepassing.  
All specifications are subject to normal commercial tolerances.  
Alle Spezifikationen unterliegen normalen Handelstoleranzen.