

## Maki

<b>Fremstillingsmåde</b>	Tuftet 3/16" cutpile	<b>Manufacturing process</b>	Tufting 3/16" cutpile
<b>Luvmateriale</b>	70% PP stainsafe - 30% PES	<b>Pile material</b>	70% PP stainsafe - 30% PES
<b>Bagside</b>	3 mm FrasterBack, synt. filt	<b>Backing</b>	3 mm FrasterBack, synthetic felt
<b>Luvvægt / m<sup>2</sup></b>	ca. 1800 gr	<b>Pile weight / m<sup>2</sup></b>	app. 1800 gr.
<b>Luvhøjde</b>	ca. 17 mm	<b>Pile height</b>	app. 17 mm
<b>Totalvægt / m<sup>2</sup></b>	ca. 3100 gr	<b>Total weight / m<sup>2</sup></b>	app. 3100 gr
<b>Totaltykkelse</b>	ca. 22 mm	<b>Total Height</b>	app. 22 mm
<b>Løkkeantal / m<sup>2</sup></b>	ca. 45.150	<b>Number of tufts / m<sup>2</sup></b>	app. 45.150
<b>Bredde</b>	ca. 400 cm	<b>Width</b>	app 400 cm
<b>Brandklasse (EN 13501-1)</b>	Efl	<b>Flammability test</b>	Efl
<b>Trinlydsdæmpnings værd</b>	ca. 28 dB	<b>Impact sound reduction</b>	ca. 28 dB
<b>Varmeledningsmodstand</b>	0,14 m <sup>2</sup> K/W	<b>Thermal conductivity</b>	0,14 m <sup>2</sup> K/W



EN 14041

EN 1307